



- 4  
 COLOURS
- 4  
 SIZES
- 3  
 FINISHES
- 5  
 SPECIAL PIECES

Regal is a beautiful collection of rectified, stone effect double loaded porcelain. Available in either matt, polished or structured and complimented by a neutral colour palette.


Regal is an extensive range which boasts 2 mosaic designs, a 300x600 etched décor, trims & door thresholds.

### COLOURS AVAILABLE

	Polished	Matt <small>Slip Resistant option also available</small>	Rock	Etched	Cubis Mosaic		Accent Glass Mosaic	Grout	Trim and Movement Joint	Door Bar: Tile/Tile Tile/Carpet
Vanilla						Vanilla & Grey Polished				
Grey						Vanilla & Grey Matt				
Ash						Ash & Smoke Polished				
Smoke						Ash & Smoke Matt				

SIZE GUIDE

800x800mm



300x600mm



600x600mm



400x800mm



SPECIAL PIECES


Thresholds  
125mmx2.5m




300x600mm



394x324mm



285x296mm





Dimensions	Multiple
Finish	Polished
Body	Double loaded porcelain
Wall/Floor	Floor & Wall
Group	Bl <sub>a</sub>
Pendulum Dry (4S)	36+
Pendulum Wet (4S)	0-24

Available Sizes		Standard	Requirement	Typical Test Value
300x600x9mm 600x600x9mm 400x800x9mm 800x800x9mm	Length & Width	ISO 10545-2	$\pm 0.6\% \leq 2\text{mm}$	Pass
	Thickness	ISO 10545-2	$\pm 5\% \leq \pm 0.5\text{mm}$	Pass
	Straightness	ISO 10545-2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	Pass
	Flatness	ISO 10545-2	$\pm 0.55\% \leq \pm 2.0\text{mm}$	Pass
	Rectangularity	ISO 10545-2	$\pm 0.5\% \leq \pm 2.0\text{mm}$	Pass
	Water absorption	ISO 10545-3	$E_b \leq 0.5\%$	Pass
	Breaking strength	ISO 10545-4	$\geq 1300\text{N}$	Ave > 2400N
	Modulus of rupture	ISO 10545-4	35 N/mm <sup>2</sup> Average min	Ave 50 N/mm <sup>2</sup>
	Resistance to deep abrasion	ISO 10545-6	$\leq 175\text{ N/mm}^2$	Ave < 140 N/mm <sup>2</sup>
	Frost Resistance	ISO 10545-12	Complies with Standard	Pass
	Thermal shock resistance	ISO 10545-9	Complies with Standard	Pass
	Resistance to Stain	ISO 10545-14	Min class 3	5
	Resistance to chemicals	ISO 10545-14	Min Class UB	UA
	Reaction to Fire	-	Floor/Wall class A1 FL/A1	Pass

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential



Dimensions	Multiple
Finish	Matt
Body	Double loaded porcelain
Wall/Floor	Floor & Wall
Group	BI <sub>a</sub>
Pendulum Dry (4S)	36+
Pendulum Wet (4S)	25-35

Available Sizes		Standard	Requirement	Typical Test Value
300x600x9mm 600x600x9mm 400x800x9mm 800x800x9mm	Length & Width	ISO 10545-2	$\pm 0.6\% \leq 2\text{mm}$	Pass
	Thickness	ISO 10545-2	$\pm 5\% \leq \pm 0.5\text{mm}$	Pass
	Straightness	ISO 10545-2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	Pass
	Flatness	ISO 10545-2	$\pm 0.55\% \leq \pm 2.0\text{mm}$	Pass
	Rectangularity	ISO 10545-2	$\pm 0.5\% \leq \pm 2.0\text{mm}$	Pass
	Water absorption	ISO 10545-3	$E_b \leq 0.5\%$	Pass
	Breaking strength	ISO 10545-4	$\geq 1300\text{N}$	Ave > 2400N
	Modulus of rupture	ISO 10545-4	35 N/mm <sup>2</sup> Average min	Ave 50 N/mm <sup>2</sup>
	Resistance to deep abrasion	ISO 10545-6	$\leq 175\text{ N/mm}^2$	Ave < 140 N/mm <sup>2</sup>
	Frost Resistance	ISO 10545-12	Complies with Standard	Pass
	Thermal shock resistance	ISO 10545-9	Complies with Standard	Pass
	Resistance to Stain	ISO 10545-14	Min class 3	5
	Resistance to chemicals	ISO 10545-14	Min Class UB	UA
	Reaction to Fire	-	Floor/Wall class A1 FL/A1	Pass

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential



Dimensions	Multiple
Finish	Structured Matt
Body	Double loaded porcelain
Wall/Floor	Floor & Wall
Group	Bl <sub>a</sub>
Pendulum Dry (4S)	36+
Pendulum Wet (4S)	36+

Available Sizes		Standard	Requirement	Typical Test Value
300x600x9mm 600x600x9mm	Length & Width	ISO 10545-2	$\pm 0.6\% \leq 2\text{mm}$	Pass
	Thickness	ISO 10545-2	$\pm 5\% \leq \pm 0.5\text{mm}$	Pass
	Straightness	ISO 10545-2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	Pass
	Flatness	ISO 10545-2	$\pm 0.55\% \leq \pm 2.0\text{mm}$	Pass
	Rectangularity	ISO 10545-2	$\pm 0.5\% \leq \pm 2.0\text{mm}$	Pass
	Water absorption	ISO 10545-3	$E_b \leq 0.5\%$	Pass
	Breaking strength	ISO 10545-4	$\geq 1300\text{N}$	Ave > 2400N
	Modulus of rupture	ISO 10545-4	35 N/mm <sup>2</sup> Average min	Ave 50 N/mm <sup>2</sup>
	Resistance to deep abrasion	ISO 10545-6	$\leq 175\text{ N/mm}^2$	Ave < 140 N/mm <sup>2</sup>
	Frost Resistance	ISO 10545-12	Complies with Standard	Pass
	Thermal shock resistance	ISO 10545-9	Complies with Standard	Pass
	Resistance to Stain	ISO 10545-14	Min class 3	5
	Resistance to chemicals	ISO 10545-14	Min Class UB	UA
	Reaction to Fire	-	Floor/Wall class A1 FL/A1	Pass

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential



Dimensions	Multiple
Finish	Slip Resistant
Body	Double loaded porcelain
Wall/Floor	Floor & Wall
Group	BI <sub>a</sub>
Pendulum Dry (4S)	36+
Pendulum Wet (4S)	36+

Available Sizes		Standard	Requirement	Typical Test Value
300x600x9mm 600x600x9mm 400x800x9mm 800x800x9mm	Length & Width	ISO 10545-2	$\pm 0.6\% \leq 2\text{mm}$	Pass
	Thickness	ISO 10545-2	$\pm 5\% \leq \pm 0.5\text{mm}$	Pass
	Straightness	ISO 10545-2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	Pass
	Flatness	ISO 10545-2	$\pm 0.55\% \leq \pm 2.0\text{mm}$	Pass
	Rectangularity	ISO 10545-2	$\pm 0.5\% \leq \pm 2.0\text{mm}$	Pass
	Water absorption	ISO 10545-3	$E_b \leq 0.5\%$	Pass
	Breaking strength	ISO 10545-4	$\geq 1300\text{N}$	Ave > 2400N
	Modulus of rupture	ISO 10545-4	35 N/mm <sup>2</sup> Average min	Ave 50 N/mm <sup>2</sup>
	Resistance to deep abrasion	ISO 10545-6	$\leq 175\text{ N/mm}^2$	Ave < 140 N/mm <sup>2</sup>
	Frost Resistance	ISO 10545-12	Complies with Standard	Pass
	Thermal shock resistance	ISO 10545-9	Complies with Standard	Pass
	Resistance to Stain	ISO 10545-14	Min class 3	5
	Resistance to chemicals	ISO 10545-14	Min Class UB	UA
	Reaction to Fire	-	Floor/Wall class A1 FL/A1	Pass

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential