




# Chime

## Technical Data Sheet

### Colours



### Finishes



Natural (N)  
R9 A

### Sizes & Formats

	30x30 cm 8.5/10.5mm	30x60 cm 9.2mm	45x45 cm 9.5mm	60x60 cm 9.5mm	60x120 cm 11mm
0001	N	N	N	N	N
0002	N	N	N	N	N
0003	N	N	N	N	N
0004	N	N	N	N	N
0005	N	N	N	N	N
0006	N	N	N	N	N
0007	N	N	N	N	N
0008	N	N	N	N	N



# Chime

## Technical Data Sheet

### Technical Details

Classification in accordance with CEN EN 14411 GRUPPO BIa UGL (ISO 13006)

#### Features

Dimension & surface quality  
Water absorption  
Flexural strength  
Modules of rupture  
Deep abrasion resistance  
Linear thermal expansion  
Thermal shock resistance  
Frost resistance  
Resistance to acids & alkalis  
Stain resistance

#### Standards

UNI EN ISO 10545-2  
UNI EN ISO 10545-3  
UNI EN ISO 10545-4  
UNI EN ISO 10545-4  
UNI EN ISO 10545-6  
UNI EN ISO 10545-8  
UNI EN ISO 10545-9  
UNI EN ISO 10545-12  
UNI EN ISO 10545-13  
UNI EN ISO 10545-14

#### Results

Conforms  
<=0.05%  
>50 N/mm<sup>2</sup>  
2500 - 6000 N  
< 140 mm<sup>3</sup>  
7x10<sup>-6</sup> °C<sup>-1</sup>  
Resistant  
Resistant  
ULA/UA  
Min Class 3 +

