



27
COLOURS

7
SIZES

2
FINISH

0
SPECIAL PIECES

Esmaltes is a small format terracotta collection, available in a large assortment of colours and 7 size formats for wall use only: 50x100mm, 75x150mm, 75x75mm, 100x100mm, 100x200mm, 50x300mm and 50x200mm.

It offers an abundance of design choices if you're looking to add a hint of colour into your scheme.

TERRACOTTA	10mm Thick		Wall/Floor	Interior/ Exterior
	Matt	*Gloss	All Tiles	All Tiles
50X100	✓	✓	Wall	Interior
75X150	✓	✓	Wall	Interior
75X75	✓	✓	Wall	Interior
100X100	✓	✓	Wall	Interior
100X200	✓	✓	Wall	Interior
50X300	✓	✓	Wall	Interior
50X200	✓	✓	Wall	Interior

* White & Black only

IN THIS RANGE



EGA-01 – BLACK GLOSS



EGA-02 – BLACK MATT




EGA-03 – ANTHRACITE



EGA-04 – GRAFITO



EGA-05 – GRIS CEMENTO



EGA-06 – GRIS CLARO



EGA-07 – WHITE GLOSS



EGA-08 – WHITE MATT




EGA-09 – CREMA



EGA-10 – VANILLA



EGA-11 – MAIZ



EGA-12 – PISTACIO



EGA-13 – AMARILLO



EGA-14 – VERDE CLARO



EGA-15 – VERDE BOTELLA



EGA-16 – AZUL COBALTO



EGA-17 – AZUL TURQUESA



EGA-18 – AZUL CIELO



EGA-19 – ROSA CLARO



EGA-20 – LILA



EGA-21 – MALVA



EGA-22 – ROSA



EGA-23 – NARANJA



EGA-24 – ROJO CORAL



EGA-25 – ROJO



EGA-26 – CARMIN



EGA-27 – CHOCOLATE

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential

Group	BIII - Ceramic
--------------	-----------------------

	Standard	Requirements	Established Values
Length & Width	ISO 10545-2	±0.6% ~ ±2mm	Conforms
Thickness	ISO 10545-2	±5% ~ ±0.5mm	Conforms
Straightness	ISO 10545-2	±0.5% ~ ±1.5mm	Conforms
Flatness	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Rectangularity	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Water absorption	ISO 10545-3	Eb >10%	Ave >10 %
Breaking strength	ISO 10545-4	≥ 600N	Ave ≥ 600 N
Modulus of rupture	ISO 10545-4	Ave Minimum 12 N/mm2	Ave 4.5 N/mm2
Thermal shock resistance	ISO 10545-9	Pass according to EN ISO 10545-1	Resistant
Frost Resistance	ISO 10545-12	Pass according to EN ISO 10545-1	Resistant
Resistance to household chemicals and swimming pool salts	ISO 10545-13	Min Class GB	GB
Resistance to high concentrations of alkalis and acids	ISO 10545-13	Declare Value	NPD
Resistance to low concentrations of alkalis and acids	ISO 10545-13	Declare Value	NPD
Resistance to Stain	ISO 10545-14	Min Class 3	Class 3
Reaction to Fire	-	Class A1 A1/FL	A1 A1/FL

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential