



13

COLOURS

2

SIZES

2

FINISHES

0

SPECIAL PIECES

Make the most of the space outdoors with VISTA20 available in a variety of stone, wood and fossil effect finishes.

These 20mm thick porcelain slabs give you an elegant appeal without the usual maintenance. Extremely hard-wearing and stain-resistant, there's a choice of installation options including fitting onto pedestals, laying onto sand, gravel, grass or laying with adhesive.

These outdoor only tiles are available in a matt or structured finishes in 600x600mm and 450x900mm (please see below for options) and are rated PTV 36+ shod foot and barefoot.

- Fossil Grey / Fossil White - 450x900mm and 600x600mm in a matt finish
- Grey Slate / Black Slate - 450x900mm in a structured finish and 600x600mm in a matt finish
- Oak / Walnut - 450x900mm in a matt finish
- Sandstone Grey / Elvert Argent / Elvert Sand / Wickliff Anthracite / Wickliff Cement / Sandstone / Limestone - 600x600mm in a matt finish

COLOURS AVAILABLE



SANDSTONE



LIMESTONE



GREY SLATE MATT



BLACK SLATE MATT



SANDSTONE GREY



GREY SLATE STRUCTURED



BLACK SLATE STRUCTURED



WICKLIFF ANTHRACITE



WICKLIFF CEMENT



OAK



ELVERT SAND




ELVERT ARGENT



FOSSIL GREY



FOSSIL WHITE



WALNUT

VISTA20 Elvert & Wickcliff

| Group | Bla – Porcelain | Standard | Requirement | Established Values |
|-------|---|--------------|-----------------------------------|----------------------------------|
| | Length & Width | ISO 10545-2 | $\pm 0.6\% \sim \pm 2\text{mm}$ | Conforms |
| | Thickness | ISO 10545-2 | $\pm 5\% \sim \pm 0.5\text{mm}$ | Conforms |
| | Straightness | ISO 10545-2 | $\pm 0.5\% \sim \pm 1.5\text{mm}$ | Conforms |
| | Flatness | ISO 10545-2 | $\pm 0.5\% \sim \pm 2.0\text{mm}$ | Conforms |
| | Rectangularity | ISO 10545-2 | $\pm 0.5\% \sim \pm 2.0\text{mm}$ | Conforms |
| | Water absorption | ISO 10545-3 | $E_b \leq 0.5\%$ | < 0.5% |
| | Breaking strength | ISO 10545-4 | $\geq 1300\text{N}$ | > 6590 N |
| | Modulus of rupture | ISO 10545-4 | Ave Minimum 35 N/mm ² | Ave Minimum 35 N/mm ² |
| | Resistance to surface abrasion | ISO 10545-7 | Declare Class | PEI 5 |
| | Thermal shock resistance | ISO 10545-9 | Pass according to EN ISO 10545-1 | Resistant |
| | Frost Resistance | ISO 10545-12 | Pass according to EN ISO 10545-1 | Resistant |
| | Resistance to household chemicals and swimming pool salts | ISO 10545-13 | Min Class GB | GA |
| | Resistance to high concentrations of alkalis and acids | ISO 10545-13 | Declare Value | GHA |
| | Resistance to low concentrations of alkalis and acids | ISO 10545-13 | Declare Value | GLA |
| | Resistance to Stain | ISO 10545-14 | Declare Value | Class 5 |
| | Reaction to Fire | - | Class A1 A1/FL | A1 A1/FL |

| Slip Resistance Characteristics | Pendulum Dry (4S Slider 96) +36 PTV | Pendulum Wet (4S Slider 96) +36 PTV |
|---------------------------------|--|--|
| FULL RANGE | ✓ | ✓ |

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

| Group | Bla – Porcelain | VISTA20 Balance | | |
|---|-----------------|-----------------|-----------------------------------|----------------------------|
| | | Standard | Requirement | Typical Test Value |
| Length & Width | | ISO 10545-2 | $\pm 0.6\% \sim \pm 2\text{mm}$ | In conformity |
| Thickness | | ISO 10545-2 | $\pm 5\% \sim \pm 0.5\text{mm}$ | In conformity |
| Straightness | | ISO 10545-2 | $\pm 0.5\% \sim \pm 1.5\text{mm}$ | In conformity |
| Flatness | | ISO 10545-2 | $\pm 0.5\% \sim \pm 2.0\text{mm}$ | In conformity |
| Rectangularity | | ISO 10545-2 | $\pm 0.5\% \sim \pm 2.0\text{mm}$ | In conformity |
| Water absorption | | ISO 10545-3 | $E_b \leq 0.5\%$ | < 0.5% |
| Breaking strength | | ISO 10545-4 | $\geq 1300\text{N}$ | > 10000N |
| Modulus of rupture | | ISO 10545-4 | Ave Minimum 35 N/mm ² | Ave min >35mm ² |
| Resistance to surface abrasion | | ISO 10545-7 | Declare Class | PEI 5 |
| Thermal shock resistance | | ISO 10545-9 | Pass according to EN ISO 10545-1 | Resistant |
| Frost Resistance | | ISO 10545-12 | Pass according to EN ISO 10545-1 | Resistant |
| Resistance to household chemicals and swimming pool salts | | ISO 10545-13 | Min Class GB | GA/GB |
| Resistance to high concentrations of alkalis and acids | | ISO 10545-13 | Declare Value | GLA/GLB |
| Resistance to low concentrations of alkalis and acids | | ISO 10545-13 | Declare Value | GHA/GHB |
| Resistance to Stain | | ISO 10545-14 | Declare Value | 5 |
| Reaction to Fire | | - | Class A1 A1/FL | A1 A1/FL |

| Slip Resistance Characteristics | Pendulum Dry (4S Slider 96) +36 PTV | Pendulum Wet (4S Slider 96) +36 PTV |
|---------------------------------|--|--|
| FULL RANGE | ✓ | ✓ |

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.