



7
COLOURS

9
SIZES

2
FINISH

0
SPECIAL PIECES


















Dawson is an extensive porcelain wall and floor range that enriches the traditional concrete effect with intense shades.

The floor options in 75x75 and 75x150 contain 20% recycled content. The floor options in 30x60, 60x60 and 45x90 contain 40% recycled content. The wall options contain 20% recycled content.



20%/ 40%

COLOURS AVAILABLE

				
WHITE (WALL/FLOOR)	PEARL (WALL/FLOOR)	SMOKE (WALL/FLOOR)	GREY (WALL/FLOOR)	TARMAC (WALL/FLOOR)
				
WHITE 3D (WALL)	PEARL 3D (WALL)	GREY 3D (WALL)		
				
WHITE (WALL)	PEARL (WALL)	SMOKE (WALL)	GREY (WALL)	
				
SAGE (WALL)	RED (WALL)			
				
SMOKE YELLOW (WALL/FLOOR)	SMOKE BLACK (WALL/FLOOR)	TARMAC JADE (WALL/FLOOR)	TARMAC BLACK (WALL/FLOOR)	

PORCELAIN	9mm Thick	9.5mm Thick	10mm Thick	20mm Thick (Outdoor Tile)	Wall/Floor	White	Pearl	Grey	Smoke	Tarmac
	Matt	Matt	Matt	Matt	Matt	Matt	Matt	Matt	Matt	Matt
300 x 600	✓				Wall & Floor	✓	✓	✓	✓	✓
600 x 600	✓				Wall & Floor	✓	✓	✓	✓	✓
450 x 900	✓				Wall & Floor	✓	✓	✓	✓	✓
750 x 750		✓			Wall & Floor	✓	✓	✓	✓	✓
750 x 1500		✓			Wall & Floor	✓	✓	✓	✓	✓
1200 x 1200	✓			✓	Wall & Floor	✓	✓	✓	✓	✓
1200 x 2400	✓				Wall & Floor	✓	✓	✓	✓	✓
Mosaic 250 x 285	✓				Wall & Floor				✓*	✓*

*This is the main colour of the mosaic

PORCELAIN	9mm Thick	Wall / Floor	White	Pearl	Grey	Smoke	Tarmac
	Matt Grip		Matt	Matt	Matt	Matt	Matt
1200 x 1200	✓	Wall & Floor	✓	✓	✓	✓	✓

CERAMIC	9mm Thick	9.5mm Thick	10mm Thick	20mm Thick (Outdoor Tile)	Wall/Floor	White	Pearl	Grey	Smoke	Red	Sage
	Matt	Matt	Matt	Matt	Matt	Matt	Matt	Matt	Matt	Matt	Matt
400 x 800 Ceramic			✓		Wall	✓	✓	✓	✓	✓	✓
400 x 800 3D Tile Ceramic	✓				Wall	✓	✓	✓			

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

Group	Bla - Porcelain
-------	-----------------

	Standard	Requirement	Typical Test Value
Length & Width	ISO 10545-2	±0.6% ~ ±2mm	In conformity
Thickness	ISO 10545-2	±5% ~ ±0.5mm	In conformity
Straightness	ISO 10545-2	±0.5% ~ ±1.5mm	In conformity
Flatness	ISO 10545-2	±0.5% ~ ±2.0mm	In conformity
Rectangularity	ISO 10545-2	±0.5% ~ ±2.0mm	In conformity
Water Absorption	ISO 10545-3	$E_b \leq 0.5\%$	$E_b \leq 0.1\%$
Breaking strength	ISO 10545-4	$\geq 1300N$	$\geq 1500N$
Modulus of rupture	ISO 10545-4	35 N/mm ² Average min	≥ 40 N/mm ²
Resistance to deep abrasion (unglazed tiles)	ISO 10545-6	≤ 175 mm ²	≤ 150 mm ²
Frost Resistance	ISO 10545-12	Complies with Standard	In Conformity
Thermal Shock Resistance	ISO 10545-9	Complies with Standard	In Conformity
Resistance to Stain	ISO 10545-13	Min class 3	5
Resistance to chemicals	ISO 10545-14	Min Class UB/ULB/UHA	UA/ULA/UHA
Reaction to Fire	-	Floor/Wall class A1 FL/A1	In Conformity

Slip Resistance Characteristics	Pendulum Dry (4S Slider 96) +36 PTV	Pendulum Wet (4S Slider 96) +36 PTV
Grip Finish	✓	✓

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

Group

Bill – Ceramic

	Standard	Requirement	Typical Test Value
Length & Width	ISO 10545-2	±0.5% ~ 2mm	In conformity
Thickness	ISO 10545-2	±10% ~ ±0.5mm	In conformity
Straightness	ISO 10545-2	±0.3% ~ ±1.5mm	In conformity
Flatness	ISO 10545-2	±0.5% ~ ±2.0mm	In conformity
Rectangularity	ISO 10545-2	±0.5% ~ ±2.0mm	In conformity
Water Absorption	ISO 10545-3	$E_b > 10\%$	$E_b > 10\% < 20\%$
Breaking strength	ISO 10545-4	$\geq 600N$	>600N
Modulus of rupture	ISO 10545-4	15 N/mm ² Average min	>15 N/mm ² Ave
Resistance to surface abrasion	ISO 10545-7	n/a	NPD
Frost Resistance	ISO 10545-12	n/a	NPD
Thermal Shock Resistance	ISO 10545-9	n/a	NPD
Resistance to Stain	ISO 10545-13	Min class 3	5
Resistance to chemicals	ISO 10545-14	Min Class GB/GLB/GHB	GA/GLA/GHA
Reaction to Fire	-	Floor/Wall class A1 FL/A1	In conformity

Recycled Content	%
Floor – 750x750, 750x1500	20%
Floor – 300x600, 600x600, 450x900	40%
Wall options	20%

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.